

Rich Media Annotations

By specifying `axf:multimedia-treatment="richmedia"`, you can embed multimedia data in your PDF as “Rich Media” annotations. For example: `<fo:external-graphic src="video.mp4" contenttype="video/mp4" axf:multimedia-treatment="richmedia">`. If `axf:multimedia-treatment="richmedia-windowed"` is specified, the content will be displayed and played in a separate window. Rich media annotations do not require external players for playback. Supported data formats and valid properties differ from when multimedia is embedded using `axf:multimedia-treatment="auto"`. For further information on ‘[axf:multimedia-treatment](#)’, please refer to the Online Manual. Rich media annotations are available with AH Formatter V6.5. This feature is supported only with PDF 1.7 or later.

`axf:multimedia-treatment="richmedia"`



`axf:multimedia-treatment="richmedia-windowed"`



`axf:media-skin-control="all"`, `axf:media-skin-color="red"`, `axf:media-skin-auto-hide="false"`

You can specify `axf:media-skin-control`, `axf:media-skin-color`, and `axf:media-skin-auto-hide` to set the appearance of the skin with the controls to play and stop the rich media.



`axf:media-activation`

`axf:media-activation` specifies when to enable or disable rich media. For details on allowed values, please refer to ‘[axf:media-activation](#)’ in the Online Manual. The following sample combines `PageOpen` (activates when the page content containing the content is opened) and `PageClose` (deactivates when the page containing the content is closed).

axf:media-activation="PageOpen PageClose"

