

PDF Bookmarks

PDF has a 'bookmark' feature for creating a hierarchical table of contents. By clicking a bookmark when viewing the PDF, you can jump to its target location. In CSS for paged media, bookmarks are created by adding `-ah-outline-*` properties to block-level elements. The level is specified by `-ah-outline-level` (1 being highest), titles are set with `-ah-outline-title`, and bookmarks can be organized using `-ah-outline-group`. These properties can be applied to any block-level HTML element like `div`, `h1`, `p`, etc.

Styling bookmarks

The style of a bookmark is independent of the style of the HTML it refers to.

Color

The `-ah-outline-color` property specifies the color of the bookmark title.

Font style

The `-ah-outline-font-style` property specifies the font style of the bookmark title. The allowed values are `'normal'` and `'italic'`.

Font weight

The `-ah-outline-font-weight` property specifies the font weight of the bookmark title. The allowed values are `'normal'` and `'bold'`.

Starting state

The `-ah-outline-expand` property specifies whether the bookmark subtree initially appears expanded or collapsed.

`-ah-outline-expand: true`

`-ah-outline-expand: true` specifies that the bookmark subtree is initially shown expanded. This is the default.

`-ah-outline-expand: false`

`-ah-outline-expand: false` specifies that the bookmark subtree is initially shown collapsed.