

## Adjustment when block in <fo:inline-container> overflows

'[axf:inline-overflow-align](#)' allows you to adjust the layout of blocks in <fo:inline-container> when they overflow. Available values are 'normal', 'start', 'end', 'left' and 'right'. The default value is 'normal', and the setting of 'axf:inline-overflow-align' is invalid when 'normal' is specified. When 'start', 'end', 'left' and 'right' are specified, blocks are shifted on the specified side of the reference area that contains <fo:inline-container>. This feature is available from AH Formatter V7.1.

By using this extension, you can adjust the layout so that the reference mark does not overflow from the content area at the beginning or end of the line, for example.

### Without the setting of 'axf:inline-overflow-align'

xx. Lorem ipsum dolor sit amet, consectetur adipiscing elit. test  
Aliquam tempus vestibulum mag ...

(#10000)

`axf:inline-overflow-align="end"`

xx. Lorem ipsum dolor sit amet, consectetur adipiscing elit. test  
Aliquam tempus vestibulum mag ...

(#10000)

### Without the setting of 'axf:inline-overflow-align'

xx. Lorem ipsum dolor sit amet, consectetur adipiscing elit.  
test Aliquam tempus vestibulum mag ...

(#10001)

`axf:inline-overflow-align="start"`

xx. Lorem ipsum dolor sit amet, consectetur adipiscing elit.  
test Aliquam tempus vestibulum mag ...

(#10001)